# B1060 BIGGER AND BETTER

RYNAN's One Inch Print Head



## **B1060** THERMAL INKJET PRINTER





#### **TECHNICAL SPECIFICATIONS**

Dimensions (L x W x H)

Weight

**Technology** 

Hi-Speed USB 2.0

**Control method** 

Control method

**External connection** 

**Build in sensor** 

Mounting brackets

**Anti-Shock** 

**Material housing** 

**Operating language** 

107.5 x 74.5 x 83mm

526.6g

Thermal Inkjet

2 USB ports

Wireless keyboard

External Sensor, External Encoder, Alarm Beacon

Available

Available

Available

Black anodized aluminum

English (Default), Finnish, Spanish, Deutsch, French, Russian, Vietnamese, Chinese,

Korean, Portuguese, Polish, Dutch, Italian, Turkish, Czech and Indonesian

#### **FEATURES**

Printability

**Maximum characters** 

Maximum messages length

Messages height

Messages storage

**Print speed** 

Resolution

Density

**Printing distance** 

Print mode

**Print direction** 

**Printable surface** 

External device

Text, Logo, Barcode 1D, Counter, Shift code, Box/Lot, Date, Time and Expiry date 150 characters / messages (Latin message)

75 characters / messages (Chinese message)

~ 3 meters

2.54 – 25.4 mm

100 messages

Maximum up to 76 m/min at 300x300 dpi

Maximum 300x300 dpi

Support: 300x300, 300x150 and 300x100 dpi

5 levels

1-6 mm

Continuous mode, Sensor mode and Repeat mode

Left to right, Right to left, Left to right reverse and Right to left reverse

Flat, Curve (pipe), Porous, Semi-Porous, Non-Porous

PLC via RS485 protocol

#### **INK AND SUBSTRATE CAPABILITIES**

Ink type Colors

Bulk Ink delivery system Ink security technology Solvent-based and Water-based inks



Available

RYNAN smart chip

### OPERATING ENVIRONMENT

Power supply Operating Temperatures

12VDC - 5A , 60W 5 - 50°C



RYNAN Technologies Pte Ltd. 60 Paya Lebar Road #10-39 Paya Lebar Square Singapore, 409051

Tel: +65 6871 8922 | www.rynantech.com | info@rynantech.com