


B1040S

“The most compact, reliable and robust Thermal Inkjet Coder for packaging printing in the market”



ANTI-SHOCK MOUNTING



RYNAN TECHNOLOGIES PTE LTD
60 Paya Lebar Road,
#10-39 Paya Lebar Square, Singapore 409051
Tel.: +65 6871 8922
Website: www.rynantech.com
E-mail: info@rynantech.com

RYNAN TECHNOLOGIES VIETNAM JSC
Longtri Hamlet, Longduc Commune,
Travinh City, Travinh Province, Vietnam
Tel.: +84 2943 746 991 - Fax: +84 2943 746 992
Website: www.rynantech.com
E-mail: info@rynantech.com

B1040S THERMAL INKJET CODER

TECHNICAL SPECIFICATIONS

Plug and print with HP45 ink cartridge (Hewlett Packard TIJ2.5 inkjet technology)
Dimensions (LxWxH): 164.35 x 85.5 x 71.6 mm / 6.47 x 3.37 x 2.82 inches
Weight: 610g (excluding cartridge)
Display: Automatic rotation 2.8" 256K colors TFT LCD display
Power Supply: AC 100V–240V, 50/60Hz, 1.4A. Maximum power consumption: 48W
New Anti-shock mounting mechanism greatly reduces the risk of damage from the manufacturing environment
New stronger and smaller skid - plate design
Throw Distance: up to 6mm

STANDARD FEATURES

New Bluetooth connectivity allows usage with Android smartphones and tablets
Stand-alone operation with Wireless keyboard direct connection
Free template design and control with PC application
AUX I/O port for external sensor, encoder and alarm kit connection
Flash USB2.0 for firmware, font and logo loading
Support external sensor - Optional not include in package
Automatic data back-up system
Nozzle switching and self-cleaning capabilities to extend cartridge lifetime
Store up to 100 messages on the printer's memory
Password protection
Automatic recognition of inks (aqueous or solvent) and application of appropriate printing parameters
New cartridge slot design for easier take in and take out
Hot-swap: Circuit protection for quick cartridge changeover
Real time report to Android devices

PRINTABILITY AND SPEEDS

Menu languages: English (default), Finnish, Spanish, German, French, Russian, Vietnamese, Chinese, Korean, Portuguese, Polish, Dutch, Italian, Turkish, Czech and Indonesian
Printable characters: Windows true fonts (with PC) and multi-languages with smart devices
Message line with predictable data: up to 6 lines from 1.69 – 12.7mm
Maximum characters input up to 150 per line
Maximum length of template up to 500mm
Printability: Alphanumeric, logos, date/time, expiry date, Julian date, shift code, counter/lot box code, multiple types of variable barcodes and database
Resolutions: Max 600x600dpi
Print speed: Max 76m/min @ 300x300dpi
Up to 5 levels of optical density

INK SOLUTIONS AND ACCESSORIES

HydraJET®2016 series - Aqueous inks for porous media - 42ml
HydraJET®2020 series - Aqueous inks for porous and semi-porous media - 42ml
HydraJET®2030 series - Aqueous inks for marking eggshells - 42ml
SoluJET®2701R - Red solvent ink for semi and non-porous media - 40ml
SoluJET®2704B - Blue solvent ink for semi and non-porous media - 40ml
SoluJET®2706K - Black solvent ink for semi and non-porous media - 40ml
Mounting accessories are available at www.rynantech.com

OPERATING TEMPERATURE AND WARRANTY

Operating temperature between 5°C and 50°C
12-month limited warranty