

Cyclic Corrosion Test Chambers (CCT-SERIES)

- ▶ 부식에 대한 환경 모의시험기로 온도, 습도, 염무, 침적, 건조 등을 통하여 생산품의 내식성, 내부식성을 시험하기 위한 환경을 제공합니다.

Provide laboratory simulation of natural corrosion and test results are similar to outside doors in researching structure, morphology and relative corrosion rates.

- Changeable size and Changing rate by CUSTOMER
- 5.7" Color Touch Screen Controller
- Constant and Programmable Type control
- Precision Control Logic (8 Zone P.I.D. control)
- Dialogue Type Parameter Input
- PC Controlling & Monitoring (Communication Option)
- Castor for Moving



MODEL		CCT-150	CCT-400	CCT-1000
VOLUME	LITER	150	392	1,000
INNER SIZE(W X D X H, mm)		500 X 500 X 600	700 X 700 X 800	1000 X 1000 X 1000
TEST METHOD	A	# SALT SPRAY, DRY, HUMIDITY, EXHAUST COMBINATION		
	B	# SALT SPRAY, DRY, HUMIDITY, EXHAUST, -20℃ LOW TEMP. COMBINATION		
	C	# SOLUTION DIPPING, DRY, HUMIDITY, EXHAUST, -20℃ LOW TEMP COMBINATION		
	MISC.	# SAE J2334, MS600-66, KSD-9502, JIS Z2371		
• ACCURACY / UNIFORMITY: ±1.0℃ / ±2.0℃ • SPRAY AMOUNT: 1.5 ± 0.5mL/hour/80cm² • AIR PRESSURE: 0.07 ~ 0.17Mpa				

Changeable size and rate by user's requirement (크기 및 용량 사용자 선정 가능)

- ▶ 기본 액세서리 (Basic Accessories)
- Shelf • castor • observation plate • spare parts (fuse, relay)
- ▶ 안전장치 (Safety Devices)
- leakage breaker • circuit breaker • over heat protector • pressure relief port
 - EOGR • fuse • low level s/w
- ▶ 옵션 (Option Items)
- phase monitoring relay • communication Port • recorder • tower lamp
 - D.A.S. • emergency call system • D.I. Water generator • GMW14872