

니켈 - 도금 황동 케이블 그랜드

타입 : Metric, EMC-Metric, PG, EMC-PG

재질 : 니켈도금된 황동

삽입 : 폴리아미드

씰링 링 : CR

오링 : NBR



온도 영역 : (-)40°C ~ (+)100°C



신흥정공(주)

Tel : 052-222-8650

Fax : 052-222-8653



METRIC / EMC-METRIC CABLE GLANDS



나사	타입	전체길이(MM)	스패너 육각(B)	전선 외경(mm)
M12 X 1.5	일반	25	14	3 - 6,5
M16 X 1.5	일반/EMC	28	17	4 - 8
M20 X 1.5	일반/EMC	31	22	6 - 12
M25 X 1.5	일반/EMC	32	24	10 - 14
M32 X 1.5	일반/EMC	34	30	13 - 18
M40 X 1.5	일반/EMC	40	40	18 - 25
M50 X 1.5	일반	46	50	22 - 32

PG / EMC-PG CABLE GLANDS



나사	타입	전체길이(MM)	스패너 육각(B)	전선 외경(mm)
PG 7	일반	25	14	3 - 6,5
PG 9	일반/EMC	29	17	4 - 8
PG 11	일반/EMC	32	20	5 - 10
PG 13.5	일반/EMC	34	22	6 - 12
PG 16	일반/EMC	34	24	10 - 14
PG 21	일반/EMC	40	30	13 - 18
PG 29	일반/EMC	48	40	18 - 25
PG 36	일반/EMC	62	50	22 - 32
PG 42	일반/EMC	62	57	30 - 38
PG 48	일반	62	64	34 - 44

신흥정공(주)