



AETP

AdvancedEngineeringTechnologyProvider



AP-4500



FIXED HEAD



ROTATING HEAD

AIR PLASMA SERIES AP-4500

AP-4500 series is upgraded from the 4000 Series.

1. Digital control of IGBT : precision control of high voltage.
2. Advanced protection of IGBT : digital protection system can save the equipment in any electric broken situation.
3. Easy plasma power control : 500 ~ 1000W by touchscreen.
4. Variety function control : air pressure limit, delay time, temperature checking.
5. Long length of cable : Max. 10m
6. Carbon brush wear sensor(at rotation head) : alarm on touchscreen at wear limit level.



AP-4500

AP-4500R

Needed Electricity	220V single-phase, 50/60 Hz, 10A, Earth connection
Needed Air pressure	5 Bar (CDA 99%)
Electric Power Consumption	< 1.5 kW
Consumed Amounts of Air	20~50ℓ/min (200mm per nozzle)
External Dimension	357(W) × 534(D) × 186(H)-Standard Size
Weight	20~24Kg
Length of Hose	Standard 4m (Max 10m)



AP-4500 MULTI FIXED DOUBLE HEAD



AP-4500R MULTI ROTATING DOUBLE HEAD



AP-4500 FIXED HEAD



AP-4500R ROTATING HEAD

AP-4500 MULTI

AP-4500R MULTI

Needed Electricity	220V single-phase, 50/60 Hz, 10A, Earth connection
Needed Air pressure	5 Bar (CDA 99%)
Electric Power Consumption	< 2.5 kW
Consumed Amounts of Air	20~50ℓ/min (200mm per nozzle)
External Dimension	377(W) × 665(D) × 278(H)
Weight	30~36 Kg
Length of Hose	Standard 4m (Max 10m)