

주식회사 우진무역

냉각팬 CATALOG



홈페이지 QR코드



우진무역

AC AXIAL FAN

Product Image Ref.	Size	Available Voltage	Hz	CFM Range	Features
	80*80*25T	115V 230V	50 60	12.00~22.00	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP55(Optional) IP68(Optional)
	80*80*38T	115V 230V	50 60	41.00~46.00	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP55(Optional) IP68(Optional)
	92*92*25T	115V 230V	50 60	24.00~37.00	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP55(Optional) IP68(Optional)
	92*92*38T	115V 230V	50 60	~48.00	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP55(Optional) IP68(Optional)
	120*120*25T	115V 230V	50 60	48.00~65.00	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP55(Optional) IP68(Optional)

* Specification can be changed without notice. * Product can be produced according to requirement.

AC AXIAL FAN

Product Image Ref.	Size	Available Voltage	Hz	CFM Range	Features
	120*120*38T	115V 230V	50 60	58.00~113.00	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP55(Optional) IP68(Optional)
	150*150*51T	115V 230V 380V	50 60	~251.00	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP55(Optional) IP68(Optional)
	160*160*55T	115V 230V	50 60	~190.00	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP55(Optional) IP68(Optional)
	172*152*40T	115V 230V 380V	50 60	~255.00	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP55(Optional) IP68(Optional)
	172*152*51T	115V 230V 380V	50 60	~251.00	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP55(Optional) IP68(Optional)

* Specification can be changed without notice. * Product can be produced according to requirement.

AC AXIAL FAN

Product Image Ref.	Size	Available Voltage	Hz	CFM Range	Features
	180*180*60T	115V 230V	50 60	~413.00	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP55(Optional) IP68(Optional)
	200*200*60T	115V 230V	50 60	258.00~420.00	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP55(Optional) IP68(Optional)
	225*225*80T	115V 230V 380V	50 60	~612.00	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP55(Optional) IP68(Optional)
	254*89T	115V 230V	50 60	~920	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP55(Optional) IP68(Optional)
	280*280*80T	115V 230V 380V	50 60	~1180.00	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP55(Optional) IP68(Optional)

* Specification can be changed without notice. * Product can be produced according to requirement.

AC CROSS FLOW FAN

Product Image Ref.	Size	Available Voltage	Hz	CFM Range	Features
	03019	115V 230V	50 60	~60.00	CE(Standard) RoHS(Standard) UL94V-0(Standard)
	03029	115V 230V	50 60	~105.00	CE(Standard) RoHS(Standard) UL94V-0(Standard)
	04015	115V 230V	50 60	~54.00	CE(Standard) RoHS(Standard) UL94V-0(Standard)
	04019	115V 230V	50 60	~68.00	CE(Standard) RoHS(Standard) UL94V-0(Standard)
	04029	115V 230V	50 60	~105.00	CE(Standard) RoHS(Standard) UL94V-0(Standard)

* Specification can be changed without notice. * Product can be produced according to requirement.

AC CROSS FLOW FAN

Product Image Ref.	Size	Available Voltage	Hz	CFM Range	Features
	06018	115V 230V	50 60	~166.00	CE(Standard) RoHS(Standard) UL94V-0(Standard)
	06024	115V 230V	50 60	~230.00	CE(Standard) RoHS(Standard) UL94V-0(Standard)
	06030	115V 230V	50 60	~270.00	CE(Standard) RoHS(Standard) UL94V-0(Standard)
	06042	115V 230V	50 60	~417.00	CE(Standard) RoHS(Standard) UL94V-0(Standard)

AC FAN

Product Image Ref.	Size	Available Voltage	Hz	CFM Range	Features
	255*99T Centrifugal	115V 230V	50 60	~982.00	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP44(Standard) IP55(Optional) IP68(Optional) Inlet Ring(Optional)
	300mm Impeller	115V 230V	50 60	~1082.98	IP54(Standard)
	350mm Impeller	115V 230V	50 60	~1453.78	IP54(Standard)
	400mm Impeller	115V 230V	50 60	~2442.59	IP54(Standard)

DC AXIAL FAN

Product Image Ref.	Size	Available Voltage	Hz	CFM Range	Features
	25*25*07T	5V 12V	-	1.66~2.69	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	25*25*10T	5V 12V 24V	-	0.63~2.07	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	30*30*07T	5V 12V	-	1.94~3.68	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	30*30*10T	5V 12V 24V	-	1.31~4.98	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	40*40*07T	5V 12V	-	3.91~6.07	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)

* Specification can be changed without notice. * Product can be produced according to requirement.

DC AXIAL FAN

Product Image Ref.	Size	Available Voltage	Hz	CFM Range	Features
	40*40*10T	5V 12V 24V	-	2.42~9.59	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	40*40*20T	5V 12V 24V	-	4.90~10.60	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	40*40*28T	12V 24V	-	8.32~25.67	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	50*50*10T	5V 12V 24V	-	7.09~12.12	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	60*60*10T	5V 12V 24V	-	11.59~17.17	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)

* Specification can be changed without notice. * Product can be produced according to requirement.

DC AXIAL FAN

Product Image Ref.	Size	Available Voltage	Hz	CFM Range	Features
	60*60*15T	5V 12V 24V	-	9.05~23.07	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	60*60*25T	5V 12V 24V	-	13.91~45.23	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	60*60*38T	12V 24V	-	36.73~45.30	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	80*80*10T	5V 12V 24V	-	15.63~31.26	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	80*80*15T	5V 12V 24V	-	22.05~68.40	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)

* Specification can be changed without notice. * Product can be produced according to requirement.

DC AXIAL FAN

Product Image Ref.	Size	Available Voltage	Hz	CFM Range	Features
	80*80*25T	5V 12V 24V 48V	-	24.25~66.20	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	80*80*38T	12V 24V 48V	-	80.40~124.74	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	92*92*25T	5V 12V 24V 48V	-	25.25~101.00	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	92*92*38T	12V 24V 48V	-	61.07~136.38	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	120*120*25T	5V 12V 24V 48V	-	33.08~178.42	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)

* Specification can be changed without notice. * Product can be produced according to requirement.

DC AXIAL FAN

Product Image Ref.	Size	Available Voltage	Hz	CFM Range	Features
	120*120*38T	5V 12V 24V 48V	-	48.89~248.03	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	140*140*51T	12V 24V 48V	-	280.00~315.00	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	172*152*52T	12V 24V 48V	-	182.18~298.70	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	200*200*60T	12V 24V 48V	-	308.40~547.70	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)

DC BLOWER FAN

Product Image Ref.	Size	Available Voltage	Hz	CFM Range	Features
	50*50*15T BLOWER	5V 12V 24V	-	2.98~5.54	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	75*75*30T BLOWER	5V 12V 24V	-	6.69~17.60	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	97*95*33T BLOWER	5V 12V 24V 48V	-	4.39~26.41	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	120*120*32T BLOWER	5V 12V 24V 48V	-	20.88~41.96	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)

DC CENTRIFUGAL FAN

Product Image Ref.	Size	Available Voltage	Hz	CFM Range	Features
	133*80T Centrifugal	24V 48V	-	~ 148.30	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) PWM(Standard) IP55(Optional) IP68(Optional) Inlet Ring(Optional)
	175*69T Centrifugal	24V 48V	-	355.50~422.80	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) PWM(Standard) IP55(Optional) IP68(Optional) Inlet Ring(Optional)
	220*73T Centrifugal	24V 48V	-	~ 460.27	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Standard) PWM(Standard) IP55(Optional) IP68(Optional) Inlet Ring(Optional)

DC CROSS FLOW FAN

Product Image Ref.	Size	Available Voltage	Hz	CFM Range	Features
	03019	12V 24V	-	~35.00	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Optional) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	03029	12V 24V	-	~46.00	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Optional) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	04019	12V 24V	-	~46.10	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Optional) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	04029	12V 24V	-	~74.54	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Optional) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)
	06018	12V 24V	-	~139.00	CE(Standard) RoHS(Standard) UL94V-0(Standard) FG(Optional) RD(Optional) PWM(Optional) IP55(Optional) IP68(Optional)

* Specification can be changed without notice. * Product can be produced according to requirement.

EC AXIAL FAN

Product Image Ref.	Size	Available Voltage	Hz	CFM Range	Features
	60*60*25T	115V&230V 겸용 (Dual Voltage)	-	21.29~26.61	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP54(Standard) IP55~68(Optional) FG(Optional) RD(Optional) PWM(Optional)
	80*80*25T	115V&230V 겸용 (Dual Voltage)	-	~47.28	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP54(Standard) IP55~68(Optional) FG(Optional) RD(Optional) PWM(Optional)
	92*92*25T	115V&230V 겸용 (Dual Voltage)	-	~61.65	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP54(Standard) IP55~68(Optional) FG(Optional) RD(Optional) PWM(Optional)
	92*92*38T	115V&230V 겸용 (Dual Voltage)	-	~82.69	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP54(Standard) IP55~68(Optional) FG(Optional) RD(Optional) PWM(Optional)

EC AXIAL FAN

Product Image Ref.	Size	Available Voltage	Hz	CFM Range	Features
	120*120*25T	115V&230V 겸용 (Dual Voltage)	-	~78.10	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP54(Standard) IP55~68(Optional) FG(Optional) RD(Optional) PWM(Optional)
	120*120*38T	115V&230V 겸용 (Dual Voltage)	-	~140.20	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP54(Standard) IP55~68(Optional) FG(Optional) RD(Optional) PWM(Optional)
	120*120*38T	115V&230V 겸용 (Dual Voltage)	-	~231.36	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP54(Standard) IP55~68(Optional) FG(Optional) RD(Optional) PWM(Optional)
	172*150*51T	115V&230V 겸용 (Dual Voltage)	-	~283.00	CE(Standard) RoHS(Standard) UL94V-0(Standard) IP54(Standard) IP55~68(Optional) FG(Optional) RD(Optional) PWM(Optional)

Other parts

Product Image Ref.	Size	Category	Material	Features
	30~280mm	Metal Cover 철망	Nikel Chrome Coated C1008 Steel Wire	RoHS(Standard)
	60~120mm	Mesh Filter 메쉬 필터	AL1050 Frame Stainless steel Mesh	RoHS(Standard)
	40~120mm	Plastic Filter 플라스틱 필터	ABS Black frame Black Polyurethane foam filter or Black Polyester foam filter	PPI45(Standard) PPI60(Optional) Flame-retardant(Optional)
	120~200mm	Ventilator Filter 빗살 필터	ABS Color frame White Polyester air filter	Flame-retardant(Optional)
	1000mm	Cord 코드	PVC 0.18*20 wires / 0.5SQ	Made In Korea(Standard)

* Specification can be changed without notice. * Product can be produced according to requirement.



IKURA FAN LINE UP

Product Image Ref.	Size	Category	Material	Features
	60~200mm	일본 브랜드 AC 축류 팬 (AC Axial fan)	Aluminum Frame Plastic or Metal Impeller	S-JET(Standard) Made in Japan(Standard)
	40~170mm	일본 브랜드 DC 축류 팬 (DC Axial fan)	Aluminum or Plastic Frame Plastic or Metal Impeller	CE(Standard) C-UL(Standard) FG(Optional) RD(Optional)
	175~400mm	일본 브랜드 AC 비 프레임 (AC None frame)	Aluminum Bracket Metal Impeller	S-JET(Standard) TP(Standard) Made in Japan(Standard)
	93~172mm	일본 브랜드 AC 블로워 (AC Blower)	Aluminum Frame Aluminum Impeller	S-JET(Standard) Made in Japan(Standard)
	120~172mm	일본 브랜드 AC 센서 제품 (AC sensor fan)	Aluminum Frame Aluminum Impeller	AC Input sensor(Optional) DC Input sensor(Optional) Made in Japan(Standard)

* Specification can be changed without notice. * Product can be produced according to requirement.



NIDEC ADVANCED MOTOR FAN LINE UP

Product Image Ref.	Size	Category	Material	Features
	60~172mm	일본 브랜드 DC 축류 팬 (DC Axial fan)	Aluminum or Plastic Frame Plastic Impeller	UL(Standard)
	50~150mm	일본 브랜드 DC 블로워 (DC Blower)	Plastic Frame Plastic Impeller	UL(Standard)
	220mm	일본 브랜드 DC 원심팬 (DC Centrifugal Fan)	Plastic Frame Plastic Impeller	UL(Standard)
	172mm	일본 브랜드 AC 축류팬 (AC Axial fan)	Aluminum Frame Plastic Impeller	UL(Standard)



BLAUBERG LINE UP

Product Image Ref.	Size	Category	Material	Features
	133~400mm	독일 브랜드 EC 원심 팬 (EC Centrifugal fan)	Plastic Backward Curved Impeller	CE(Standard) RoHS(Standard) Made in Europe(Standard) PWM+FG(Standard) IP55(Standard) Inlet Ring(Optional)
	108~200mm	독일 브랜드 EC 원심 팬 (EC Centrifugal fan)	Galvanized Steel Forward Curved Impeller	CE(Standard) RoHS(Standard) Made in Europe(Standard) PWM+FG(Standard) IP55(Standard) Inlet Ring(Optional)
	120~146mm	독일 브랜드 EC 블로워 (EC Blower)	Sheet steel Frame Galvanized steel Impeller	CE(Standard) RoHS(Standard) Made in Europe(Standard) PWM+FG(Standard) IP55(Standard) Dual Inlet(Optional) Single Inlet(Optional)
	200~450mm	독일 브랜드 AC 축류 팬 (AC Axial Fan)	Coated Steel Impeller	CE(Standard) RoHS(Standard) Made in Europe(Standard)
	133~250mm	독일 브랜드 EC 플러그 팬 (EC Plug Fan)	Plastic Impeller Sheet steel Inlet Ring Sheet steel Case	CE(Standard) RoHS(Standard) Made in Europe(Standard) PWM+FG(Standard) IP55(Standard)

* Specification can be changed without notice. * Product can be produced according to requirement.



우진무역



IKURA FAN



Nidec
All for dreams

주식회사 우진무역

판매팀 TEL : 010-6796-4001 / 070-4237-2001

판매팀 MAIL : woojinfan@naver.com

지점 안내

우진무역 구로점 : 서울 구로구 경인로53길 15, 구로중앙유통단지 나동 3408호

우진무역 종로점 : 서울 종로구 청계천로 151-7

우진무역 부산점 : 부산 사상구 과감로 37, 3동 125호(부산산업용품유통상가)



홈페이지 QR코드