



SITOP UPS500S/DC/24VDC/15A/2.5KWS

SITOP UPS500S maintenance-free uninterruptible power supply with USB interface basic device 2.5 kWs input: 24 V DC output: 24 V DC/15 A degree of protection IP20

input	
supply voltage at DC rated value	24 V
input voltage at DC	22 ... 29 V
adjustable response value voltage for buffer connection preset	22.5 V
adjustable response value voltage for buffer connection	22 ... 25.5 V; Adjustable in 0.5 V increments
input current at rated input voltage 24 V rated value	15.2 A; + approx. 2.3 A with empty energy storage (capacitor)
memory	
type of energy storage	with capacitors
design of the mains power cut bridging-connection	15 A for 3 s or 10 A for 6 s or 5 A for 15 s or 2 A for 38 s; longer buffering times with expansion modules
buffering time in the event of power failure	0.05 min
energy content of energy storage	2.5 kW.s
output	
output voltage	
• in normal operation at DC rated value	24 V
• in buffering mode at DC rated value	24 V
formula for output voltage	24 V ± 3 %
startup delay time typical	0.6 s
voltage increase time of the output voltage typical	25 ms
output voltage in buffering mode at DC	24 ... 24.7 V
output current	
• rated value	15 A
• in normal operation	0 ... 15 A
• in buffering mode	0 ... 15 A
peak current	25 A
property of the output short-circuit proof	Yes
charging current	1 A, 2 A
efficiency	
efficiency in percent	
• at rated output voltage for rated value of the output current typical	97.5 %
power loss [W]	
• at rated output voltage for rated value of the output current typical	9 W
supplied active power typical	360 W
protection and monitoring	
product function	
• reverse polarity protection against energy storage unit polarity reversal	Yes
• reverse polarity protection against input voltage polarity reversal	Yes

display version	<ul style="list-style-type: none"> for normal operation in buffering mode 	Normal operation: LED green (OK), floating changeover contact "OK/Bat" to setting "OK" ("OK" means: Voltage of the supplying power supply unit is greater than cut-in threshold set at the DC UPS module); lack of buffer standby: LED red (ALARM), floating changeover contact "ALARM/BAT" to setting "ALARM"; energy storage > 85%: LED green (BAT > 85%), floating NO contact "BAT > 85" closed; permissible contact current capacity: DC 60 V/1 A or AC 30 V /1 A
		Buffered mode: LED yellow (BAT), floating changeover contact "OK/BAT" to setting "BAT"; Prewarning buffer end after expiry of 80% of the available buffer time: LED red (ALARM), floating changeover contact "ALARM/BAT" to setting "ALARM"; Energy storage > 85%: LED green (BAT > 85%), floating NO contact "BAT > 85" closed
interfaces		
product component PC interface	Yes	
product function communication function	No	
design of the interface	USB	
safety		
galvanic isolation between input and output	No	
operating resource protection class	Class III	
protection class IP	IP20	
standard		
• for emitted interference	EN 55022 Class B	
• for interference immunity	EN 61000-6-2	
standards, specifications, approvals		
certificate of suitability		
• CE marking	Yes	
• UL approval	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259	
• CSA approval	Yes; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)	
• EAC approval	Yes	
MTBF at 40 °C	638 570 h	
standards, specifications, approvals marine classification		
shipbuilding approval	Yes	
Marine classification association		
• American Bureau of Shipping Europe Ltd. (ABS)	Yes	
• Det Norske Veritas (DNV)	Yes	
standards, specifications, approvals Environmental Product Declaration		
Environmental Product Declaration	Yes	
global warming potential [CO2 eq]		
• total	328.8 kg	
• during manufacturing	46.4 kg	
• during operation	281.6 kg	
• after end of life	0.74 kg	
ambient conditions		
ambient temperature		
• during operation	0 ... 60; with natural convection	
• during transport	-40 ... +70	
• during storage	-40 ... +70	
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation	
connection method		
type of electrical connection	screw terminal	
• at input	24 V DC: 2 screw terminals for 1 ... 4 mm ² /17 ... 11 AWG	
• at output	24 V DC: 4 screw terminals for 1 ... 4 mm ² /17 ... 11 AWG	
• for control circuit and status message	10 screw terminals for 0.5 ... 2.5 mm ² /20 ... 13 AWG	
mechanical data		
width x height x depth of the enclosure	120 x 125 x 125 mm	
installation width x mounting height	120 mm x 225 mm	
required spacing		
• top	50 mm	
• bottom	50 mm	
• left	0 mm	
• right	0 mm	
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15	
• DIN-rail mounting	Yes	

• S7 rail mounting	No
• wall mounting	No
housing can be lined up	Yes
net weight	1 kg
accessories	
electrical accessories	Extension module SITOP UPS501S
further information internet links	
internet link	<ul style="list-style-type: none"> • to website: Industry Mall • to web page: selection aid TIA Selection Tool • to web page: power supplies • to website: CAx-Download-Manager • to website: Industry Online Support
additional information	
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)
security information	
security information	<p>Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)</p>

Classifications			
	Version	Classification	
eClass	14	27-04-07-05	
eClass	12	27-04-07-05	
eClass	9.1	27-04-07-05	
eClass	9	27-04-07-05	
eClass	8	27-04-06-90	
eClass	7.1	27-04-06-90	
eClass	6	27-04-06-90	
ETIM	9	EC000382	
ETIM	8	EC000382	
ETIM	7	EC000382	
IDEA	4	4149	
UNSPSC	15	39-12-10-11	

Approvals Certificates	
General Product Approval	Marine / Shipping



[Manufacturer Declaration](#)

[Declaration of Conformity](#)



Marine / Shipping	Environment
--------------------------	--------------------



last modified:

4/9/2025