

Tray Feeding System

Model Name		STF100S	STF100N	STF100D
Applicable Chip Mounter		SM411F, SM421, SM321	SM411F, SM421, SM321, CP45NEO	
Machine Location		Right	Rear	Rear
Tact Time		3sec		
Tape Feeder Slot Occupation		0 Slot	34 Slot	
Feeding Accuracy		±0.2mm@3σ		
Component Range (Max. Height)		H = 9.5mm (H = 25.4mm, if pallet are loaded in every other slot)		
Pallet Slot Pitch		14mm		
Non-Stop Operation		○	○	○
Utility	Power	AC100 / 110 / 120 / 200 / 220 / 240V (50/60Hz, 1Phase)		
	Air Consumption	None		
Dimension (mm)	Tray	Min. 200(L) x 100(W)	Min. 200(L) x 100(W)	
		Max. 322.6(L) x 136(W)	Max. 340(L) x 272(W)	
	PCB	Min. 50(L) x 40(W)	Min. 50(L) x 40(W)	
		50(L) x 30(W) (Option)	50(L) x 30(W) (Option)	
		Max. 460(L) x 400(W)	Max. 460(L) x 400(W) / 510(L) x 460(W) / 610(L) x 510(W)	
	External	938(L) x 1,552(D) x 1,344(H)	1,307(L) x 500(D) x 1,300(H)	1,350(L) x 503(D) x 1,442(H)
Weight (kg)		Approx.250		

* The specifications in this catalogue may be changed without prior notice for quality improvement



STF 100S

Non-Stop Side Tray Feeder



STF 100N

Non-Stop Tray Feeder

STF 100D

Non-Stop Dual Tray Feeder



STACK TRAY

고객주문형

