

Magazine Loader

SLD-120



특징

- Error 메시지 표시 및 특수기능키 내장
- Magazine 상하 2종의 완벽한 고정 장치
- Board 투입 Pitch(10mm, 20mm, 30mm, 40mm) 선택의 다양화
- Line 구성에 따라 어떤 장비와도 연결 가능
- YL형은 2열 Ball Screw Up/Down 방식 기본적용(특허 등록)
- Pusher Cylinder 위치 변경 용이
- SMEMA INTERFACE

Features

- Error message display and special ability key
- Perfect fixing with magazine dual clamp unit
- Various feeding pitch 1~4 steps(10m/m, 20m/m, 30m/m, 40m/m)
- Possible to line with various kinds of machine
- YL size double ball screw up down unit(patent application)
- Convenient to change position of pusher cylinder
- SMEMA INTERFACE

Option

- Safety Cover-CE
- Magazine change overtime(18 seconds)
- Output buffer conveyor
- Up/Down Soft start/Stop(Inverter)
- Touch screen
- Possible to change magazine loading volume
- Prevention function from PCB damage
- Space saving type(90°)

Specifications

MODEL	PCB SIZE (W)×(L)	MAGAZINE CAPACITY		PCB FEED PITCH	PCB INPUT HEIGHT	POWER SUPPLY	AIR	DIMENSION (L×W×H)	WEIGHT
SLD-120	50×50~250×330	120	UPPER:1	4 TYPES 10~40mm	900±30mm	AC100~240V 50~60Hz (V,Hz Option)	5.0Kg/air	1170×823×1150	160kg
SLD-120Y	50×50~330×440		LOWER:2					1490×840×1150	180kg
SLD-120L	50×50~390×510	120	UPPER:1					1735×890×1150	200kg
SLD-120X	50×50~460×510		LOWER:2					1735×980×1150	210kg
SLD-120X2	50×50~460×620	120	UPPER:1					1955×980×1150	230kg
SLD-120F	50×50~460×800		LOWER:2					1990×980×1150	240kg

Magazine Loader (CE)

SLD-120CE



특징

- Error 메시지 표시 및 특수기능키 내장
- Magazine 상하 2종의 완벽한 고정 장치
- Board 투입 Pitch(10mm, 20mm, 30mm, 40mm) 선택의 다양화
- Line 구성에 따라 어떤 장비와도 연결 가능
- YL형은 2열 Ball Screw Up/Down 방식 기본적용(특허 등록)
- Pusher Cylinder 위치 변경 용이
- SMEMA INTERFACE

Features

- Error message display and special ability key
- Perfect fixing with magazine dual clamp unit
- Various feeding pitch 1~4 steps(10m/m, 20m/m, 30m/m, 40m/m)
- Possible to line with various kinds of machine
- YL size double ball screw up down unit(patent application)
- Convenient to change position of pusher cylinder
- SMEMA INTERFACE

Option

- Safety Cover-CE
- Magazine change overtime(18 seconds)
- Output buffer conveyor
- Up/Down Soft start/Stop(Inverter)
- Touch screen
- Possible to change magazine loading volume
- Prevention function from PCB damage
- Space saving type(90°)

Specifications

MODEL	PCB SIZE (W)×(L)	MAGAZINE CAPACITY		PCB FEED PITCH	PCB INPUT HEIGHT	POWER SUPPLY	AIR	DIMENSION (L×W×H)	WEIGHT
SLD-120CE	50×50~250×330	120	UPPER:1	4 TYPES 10~40mm	900±30mm	AC100~240V 50~60Hz	5.0Kgf/cm ²	1170×653×1650	200kg
SLD-120YCE	50×50~330×440		LOWER:2					1490×840×1650	220kg
SLD-120LCE	50×50~390×510	120	UPPER:1			1735×890×1150		240kg	
SLD-120XCE	50×50~460×510		LOWER:2			1735×980×1150		250kg	
SLD-120X2CE	50×50~460×620	120	UPPER:1			1955×980×1150		270kg	
SLD-120FCE	50×50~460×800		LOWER:2			1990×980×1150		310kg	